

Flow-Pack

- 100% stainless steel
- Available in Q1, Q3, Q7 mono & multirounds formats
- Available in 10", 20", 30" length
- Bottled lid or clamp closure (depending on sizes)
- High cleanliness for operators and cleaning phases
- Compliant with DESP 2014/68/CE



The range of PackFlow housing is compatible with the packed filters and able to manage high flow rates. Dedicated to fluids with high viscosity, high contaminants loads, or gels, they are able to resist to high pressure losses. They have been conceived to protect the operator during maintenance and cleaning phases. They reduce contamination of the working environment and risks of cross contamination.

✓ Materials

Housing : 316L
In/Out connexions : 1/2" Gaz
Vent : Lateral 1/4" Gaz

✓ Conditions de service

Max. operating temperature : 70°C
Max. operating pressure : 0 - 10 bar

✓ Certifications

DESP : Compliant with European directive **2014/68/CE**

✓ Applications



CHEMICALS
 Chemicals, inks, resins, coatings



AUTOMOBILE
 Paints

✓ Ordering code (create your code)

Range	Nb of cartridges	-	Lenght
FWP	1 (for 5", 10" or 20")		05 (5")
	3 (for 20" or 30")		10 (10")
	7 (for 20" or 30")		20 (20")
			30 (30")
<i>Example : FWP3-20</i>			